New Products



Sensor appliance
The Maverick IP sensor appliance designed by Mamac Systems Inc. allows personnel to monitor and control it from any Web browser and send e-mail alerts. The unit can log data in CSV format as well as display it as an adjustable graph. There is no additional software required to connect to the device, which can plug into any hub or router. www.mamacsys.com #9

Low voltage wires

Honeywell International's line of UL listed PVC and plenum low-voltage wires are designed to optimize performance of thermostat controls, doorbells, and heating and air conditioning equipment. The wires are compatible with both digital and analog thermostats. Available in various colors, these solid copper conductors measure from 18 to 20 AWG. www.honeywell.com #10

Mass notification system

OnAlert created by Inova Solutions provides an economical Ethernetpowered LED display for emergency notification. The unit allows for e-mail messages composed in emergency situations to be simultaneously displayed on LED signs throughout any facility. The wallboards default to a display of time and date when there is no emergency. The system can be plugged directly into an Ethernet jack and can receive both time updates as well as power from the connection. www.inovasolutions.com #11

Are you getting phone support when you really need field support?



EMISSIONS SOLUTIONS

MIRATECH offers more field support for Power Gen emission control products - NSCR Catalysts, Diesel Particulate Filters, SCR Catalysts and controls. Worry about running your business, not about getting stuck on hold. Call MIRATECH at 1-800-640-3141.



TRUST MIRATECH FOR BETTER CUSTOMER SUPPORT, BETTER PRODUCTS, BETTER EMISSIONS.

Visit: MIRATECHCORP.com

Contact: info@miratechcorp.com

Call: 800.640.3141

MIRATECH CORPORATION • 4224 SOUTH 76TH EAST AVENUE • TULSA, OKLAHOMA 74145-4712 MIRATECHCORP.COM • 800.640.3141

Fire alarm IP communications

The IPDACT-2UD from Fire-Lite allows operators to download alarm panel data and upload information such as program updates from a networked computer or over the Internet. The unit transmits all information digitally via TCP/IP and is secured with the industry's highest level of encryption. The fully digital transmission eliminates common dropouts in communications caused by signal noise. www.firelite.com #12

Air handling unit

The Senior series of water source heat pumps designed by Change Air Products & Service Ltd. can provide up to 30,000 BTU/hr of recovered energy through the addition of a desiccant wheel. Supply air velocities range from 1,000 to 2,000 cfm. An economizer damper with full bypass of the recovery wheel is standard with the energy recovery options. www.changeair.com #13