

Convinced that all temp sensors are same?

Probe attached to enclosure with friction lock between nylon and steel

- Nylon 6/6 fitting-rated at 185°F (85°C)
- Sensor-rated at 250°F (121°C)

C7041B2005/U

Uneven sealing surface due to screw head protruding from base

Utility (handy) box and light fixture bracket available at corner hardware store

No strain or relief or secondary seal

Self-tapping screw hole

Self-tapping screws have to be removed to gain access

Probe secured to enclosure with patented steel flange crimp

Sealing gasket to eliminate leaky ducts wasting energy

TE-702-B-17-B

Self-clinching corrosion-free aluminum nut and nickel-plated screw

Rising case terminal block

Application-specific tooled enclosure, cover and bracket

Strain relief and double secondary moisture seal

Conduit knock-out

Keyed cover — *loosen screw and swing out of way!*

All MAMAC 700 Series Temperature sensors are vibration and shock tested to MIL STD 810, corrosion and lifecycle tested to ASTM B845, Method H. CE, C-Tick, and UL approved. Made in U.S.A.

MAMAC 700 Series Temperature Sensors are ***guaranteed for life*** against moisture migration!

No wonder OEMs exclusively specify MAMAC Sensors.



www.mamacsys.com

USA: 800-843-5116 Canada: 800-551-7120 United Kingdom: 01384-271113
 Australia: 800-88-2691 Singapore: 656-3927273